

ALPHA 65

Product Specification Sheet

Alpha 65 is equipped with a 1" (25mm) tweeter and a 6 1/2" (16.5cm) woofer. It features a 35W amplifier for the tweeter and a 70W amplifier for the woofer, and has a frequency response of 40Hz to 22kHz (+/- 3dB). This model performs just as well with instrumental music as with electronic music, and is characterised by its great versatility.



Key points

- Low directivity: keeps the same sound throughout the room
- Damping and rigidity: neutrality, no distortion
- Tonal balance is identical at low and high volumes; low sensitivity to the wall effects
- Connect up to 2 audio sources
- Optimal acoustic integration
- Reduced power consumption

Type	Monitoring Alpha 65
Frequency response (+/- 3dB)	40Hz - 22kHz
Power	105W (70W+35W)
Maximum SPL	106dB SPL (pic @ 1m)
Electronic section	
Inputs Connectors	XLR balanced 10kOhms RCA unbalanced 10kOhms with sensitivity compensation
LF amplifier stage	70W, class AB
HF amplifier stage	35W, class AB
Standby mode Standby	After about 30 minutes without using the monitor By signal detection >3 mV
Activation of the monitor	
Power supply (The voltage can not be modified)	220-240V (fuse T800mAL/250V) or 100-120V (fuse T1.6AL/250V)
Connection	IEC inlet and detachable power cord

User controls	
Sensitivity	Adjustable, 0 or +6dB
LF shelving (0 - 300Hz)	Adjustable, +/-6dB
HF shelving (4.5 - 22kHz)	Adjustable, +/-3dB
Power ON/OFF	Switch on rear panel
Standby mode power consumption	< 0,5W
Indicators	Power ON/OFF LED - Standby LED
Transducers	
Woofer	6.5" (16.5cm) drive unit - Polyglass cone
Tweeter	1" (25mm) drive unit Aluminium inverted dome
Cabinet	
Construction	0.6" (15mm) MDF
Finish	Vinyl and Black painting
Dimensions with 4 rubber pads (HxWxD)	13.7x9.9x12.2" (348 x 252 x 309mm)
Weight	20.7lb (9.4kg)